

MUM-14

Multipurpose Night Sight





MUM-14 is a multipurpose night vision system that can be used as a night sight (along with a sight collimator or day sight), a monocular attachable to a helmet or a face mask, a diver device (attached to goggles), a stereoscopic NVG binocular (via a binocular adapter), a night scope (using magnifier of 3x, 4x or 5x magnification) or as a powerful intelligence tool (with a compass, laser illuminator or mounted to a camera). MUM-14 can be equipped with an I2 tube of all generations, commercially available batteries (AA or CR123) and a wide range of mechanical interfaces.

PRAMACOM - HT, spol. s r.o.

www.infrared.cz

infrared@infrared.cz

- truly multipurpose
- watertight to 20 m
- variety of accessories: magnifier, compass, periscope, lens for illumination focusing...
- MIL-STD-1913 quick release
- AA or CR123 batteries power supply
- rugged system (MIL specifications)
- used in a quantity 5,000 pc+
- compatible with thermal imaging or SWIR clip-on adapters
- manufactured and serviced in the Czech Republic

tel.: +420 220 199 520

tel.: +420 588 188 401



MUM-14

Specifications



Parameter	MUM-14	
	Night Sight	Night Vision Monocular
Field of view	13° (with 3x magnifier)	40° (1x magnification)
Man detection	400m (with 3x magnifier)	150m (1x magnification)
Focusing	80 m to ∞	25cm to ∞
Exit pupil distance from eye	35mm (rubber eye cup)	35mm
Mounting	MIL-STD-1913	face mask
Image intensifying tube	3 rd GEN / XD-4, XR5, INTENS, 4G	
Dioptric correction	- 6D to + 4D	
Indicators	low battery and IR illumination ON	
IR illumination	yes (optional attachment of IR illumination focusing lens)	
Power / battery life	1x AA battery or 1x CR123 battery / 72 hours	
Magnifier	x1, x3, x4 or x5 magnification	
Operating / storage temperature	- 40°C to + 50°C / - 51°C to + 85°C	
Mechanical resistance / watertightness	shock and vibrations resistance / 20m	
Weight / dimensions	800g / 135 x 75 x 60mm	260g / 107,5 x 68,5 x 49,5mm





quick-release weapon mount

mounted to helmet





MUM-14/ day sight adapter



tel.: +420 588 188 401